Dart Aerospace Ltd. Friday, 01/05/2009 10:02:43 AM Date: USET: Jean-Luc Menard **Process Sheet** Customer : CU-DAR001 Dart Helicopters Services **Drawing Name** : BRACKET ASSEMBLY Job Number : 47647 : 10281 **Estimate Number** P.O. Number Part Number : D3183043 : 01/05/2009 - D3183 REV C1 This Issue S.O. No. : **Drawing Number** Prsht Rev. : NC : N/A Project Number : // MACHINED PARTS : C1 First Issue Type **Drawing Revision** : 46030 **Previous Run** Material **Due Date** : 08/05/2009 Qty: 6 Um: Each Written By Checked & Approved By Comment : Est Rev:Pick;A 04.02.18 New issue KJ/DS Est Rev:B Changed Mat Size 08-06-26 JLM Verified By:EC **Additional Product** Job Number: **Machine Or Operation:** Seq. #: Description: 1.0 M174B1500X02250 17-4 SS Bar 1.50 X2,250 Comment: Qty.: 0.4812 f(s)/Unit Total: 2.8873 f(s) Material: 17-4 SS Bar per AMS 5604/5643 (M17-4-B1.500x02.25) Identify for D3183-043 Batch: M10\309 2.0 BAND SAW Comment: BAND SAW Cut blanks: (1.500" x 2.250") 5.500" long 3.0 HAAS1 Comment: HAAS CNC VERTICAL MACHINING #1 1-Machine D3183-3 as per Folio FA322 and Dwg D3183 Identify as D3183-3 2-Deburt 3-Scribe batch number 4.0 INSPECT PARTS AS THEY COME OFF MACHINE QC2

Comment: INSPECT PARTS AS THEY COME OFF MACHINE

User: Jean-Luc Menard **Process Sheet** Customer: CU-DAR001 Dart Helicopters Services Drawing Name: BRACKET ASSEMBLY Job Number: 47647 Part Number: D3183043 Job Number: Seq. #: Description: **Machine Or Operation:** 5.0 SECOND CHECK QC8 Comment: SECOND CHECK 09/05/04 6.0 D312121 Bolt Comment: Qty.: 2.0000 Each(s)/Unit Total: 12.0000 Each(s) Pick: **Qty Part Number** Description Batch Bolt 46739 2 D3121-21 7.0 D3183045 Bearing Assembly Comment: Qty.: 2.0000 Each(s)/Unit Total: Pick: **Qty Part Number** Description Batch 2 D3183-045 Bearing Ass 8.0 Comment: SMALL & MEDIUM FAB RESOURCE 1 Assemble D3183-043 as per Dwg D3183. 9.0 QC5 INSPECT WORK TO CURRENT S Comment: INSPECT WORK TO CURRENT STEP 10.0 PACKAGING 1 PACKAGING RESOURCE #1 Comment: PACKAGING RESOURCE #1 Identify and Stock Location: 11.0 FINAL INSPECTION/W/O RELEASE QC21 Comment: FINAL INSPECTION/W/O RELEASE Job Completion

Form: rprocess

Date:

Page 2

Friday, 01/05/2009 10:02:43 AM

W/O:		WORK ORDER CHANG	ES				
DATE STEP		PROCEDURE CHANGE	Ву	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector
						,	
	<u> </u>						

Part No: 183-043 PAR #:	Fault Category:	NCR: Yes No DQA:	Date:09/05/14
Resolution:	Disposition:	QA: N/C Closed:	Date:

NCR: 47647		W	ORK OR	DER NON-CONFORMANCE	(NCR)							
	`	Description of NC	Description of NC Corrective Action Section B					Description of NC Corrective Action Section B		Verification	Approval	Ammuoval
DATE	STEP	Section A Initial Action Desc		Action Description Chief Eng	otion Sign & Section Section		Chief Eng	Approval QC Inspector				
21-16	<u>1</u> 2 80	<u> </u>	Posicia	No Replace Que	Ef5 09/05/06	07(05/12	bsiun	Sorlatas				
		R.C. wasn't checked Duran's madning hack of Attachin	psim	And Qly @ Bearen AS D3183-043. unale la reman	B / 01/0700	01/05/12	brion	Solution				

NOTE: Date & initial all entries

DART AEROSPACE LTD	Work Order:	47641
Description: Bracket	Part Number:	D3183-3
Inspection Dwg: D3183 Rev: C1		Page 1 of 1

FIRST ARTICLE INSPECTION CHECKLIST

X First Article Prototype

Drawing Dimension Tolerance Dimension Dimension Ro.190 +/-0.030 . ?\tau .063 . \tau .063 . \tau .063 . \tau .083 . \tau .083 . \tau .083 . \tau .083 . \tau .096 . \tau		<u> </u>					
R0.190 +/-0.030 ./90 / R0.063 +/-0.010 .065 - 0.182 +/-0.010 .075 / 0.100 +/-0.010 .075 / 0.100 +/-0.010 .076 / 0.201 x 0.100 +/-0.010 .076 / 0.182 +/-0.010 .201 x .076 / 0.218 +/-0.010 .201 x .077 / 0.218 +/-0.010 .201 x .077 / 0.218 +/-0.010 .203 x .077 / 0.218 +/-0.010 .203 x .077 / 0.218 +/-0.010 .203 x .077 / 0.219 +/-0.010 .203 x .077 / 0.210 x 0.100 +/-0.010 .203 x .077 / 0.201 x 0.100 +/-0.010 .203 x .077 / 0.392 +0.002/0.000 .393 / R0.19 +/-0.030 .190 / 0.3954 +/-0.010 .160 / R0.19 +/-0.030 .190 / 0.162 +/-0.010 .160 / R0.19 +/-0.030 .190 / 0.266 / 0.2080 +/-0.030 .250 / 4.26 +/-0.030 .250 / 4.26 +/-0.030 .250 / 0.36 +/-0.030 .360 / 0.36 +/-0.030 .360 / 0.36 +/-0.030 .360 / 0.36 +/-0.030 .360 / 0.36 +/-0.030 .360 / 0.36 +/-0.030 .360 / 0.36 +/-0.030 .360 / 0.36 +/-0.030 .360 / 0.36 +/-0.030 .360 / 0.36 +/-0.030 .360 / 0.36 +/-0.030 .360 / 0.36 +/-0.030 .360 / 0.36 +/-0.030 .360 / 0.36 +/-0.030 .360 / 0.36 +/-0.030 .360 / 0.36 +/-0.030 .360 / 0.36 +/-0.030 .360 / 0.615 +/-0.010 .565 / 0.0162 +/-0.010 .565 / 0.0162 +/-0.010 .565 / 0.036 +/-0.0	1	Tolerance		Accept	Reject	1	Comments
R0.063			l		-	•	
0.182				/	<u> </u>		
0.070				ļ~			
0.100			.181				
Ø0.201 x 0.100							
0.182 +/-0.010 184 /- 5.32 +/-0.030 ≤.328 /- 5.036 +/-0.010 5.036 /- 2.120 +/-0.010 2./20 /- 1.290 +/-0.010 3.68 /- 0.365 +/-0.010 3.68 /- 0.218 +/-0.010 3.68 /- 1.030 +/-0.010 1.030 /- 1.090 +/-0.030 /- 1.090 +/-0.030 /- 1.090 +/-0.030 /- 0.201 x 0.100 +/-0.010 1.03 /- 0.201 x 0.100 +/-0.010 1.03 /- 0.786 +/-0.010 1.03 /- 0.786 +/-0.010 1.03 /- 0.392 +0.002/-0.000 3.93 /- 0.162 +/-0.010 1.60 /- R0.19 +/-0.030 190 /- R0.25 +/-0.030 3.50 /- 4.26 +/-0.030 3.680 /- 2.080 +/-0.030 3.680 /- 1.155 +/-0.010 1.57 /- 0.162 +/-0.010 1.57 /- 0.162 +/-0.010 1.55 /- 0.162 +/-0.010 1.55 /- 0.162 +/-0.010 1.55 /- 0.162 +/-0.010 1.55 /- 0.162 +/-0.010 1.55 /- 0.162 +/-0.010 1.55 /- 0.162 +/-0.010 1.55 /- 0.162 +/-0.010 1.55 /- 0.162 +/-0.010 1.55 /- 0.162 +/-0.010 1.55 /- 0.162 +/-0.010 1.55 /- 0.162 +/-0.010 1.55 /- 0.162 +/-0.010 1.55 /- 0.162 +/-0.010 1.55 /- 0.162 +/-0.010 1.55 /- 0.162 +/-0.010 1.55 /- 0.162 +/-0.010 1.55 /- 0.0615 +/-0.010 1.55 /-							
5.32			.201 × .098				
5.036 +/-0.010 5.036 / 2.120 +/-0.010 2./20 / 1.290 +/-0.010 2./20 / 1.290 +/-0.010 1.368 / 2.120 / 1.0365 +/-0.010 1.368 / 2.120 / 2.128 +/-0.010 1.2(4 / 2.120 / 2.128 +/-0.010 1.2(4 / 2.120 / 2.							
2.120 +/-0.010							
1.290							
0.365				/			
0.218	<u> </u>						
1.030 +/-0.010 /.030 /.890 /				1			
1.90			.214	i .			
1.012	1.030	+/-0.010					
1.012	1.90	+/-0.030	1.890	V.			
0.786	1.012	+/-0.010	1.012				
Mole	Ø0.201 x 0.100	+/-0.010	203 x .097	~			
R0.19	0.786	+/-0.010	.789	✓			
R0.19	Ø0.392	+0.002/-0.000	. 393				
0.162 +/-0.010 , /6〇 R0.19 +/-0.030 . 1句	R0.19	+/-0.030	190				
0.162 +/-0.010 , /6〇 R0.19 +/-0.030 . 1句	3.954	+/-0.010	3.954				
R0.25 +/-0.030 /350 / 4.266 / 4.266 +/-0.030 分の数 / .266 / 2.080 +/-0.030 分の数 / .266 / 1.155 +/-0.010 以 いって / .257 / .25	0.162	+/-0.010	,760				
R0.25 +/-0.030 /350 / 4.266 / 4.266 +/-0.030 分の数 / .266 / 2.080 +/-0.030 分の数 / .266 / 1.155 +/-0.010 以 いって / .257 / .25	R0.19	+/-0.030	.190	~			4
4.26 +/-0.030	R0.25	+/-0.030		7			_
2.080 +/-0.030 2.080 -	4.26	+/-0.030					
1.155	2.080	+/-0.030		1			
0.162 +/-0.010 /57 V 0.36 +/-0.030 /350 V 0.615 +/-0.010 /して	1.155	+/-0.010					
0.36 +/-0.030 ,350 V 0.615 +/-0.010 ,615 V	0.162	+/-0.010					
0.615 +/-0.010 ,615 /	<u> </u>			1/			
				/			
	0.435	+/-0.010	.437	1			
0.200 +/-0.010 .205				 			
0.381 +/-0.010 . 3원			1381				
0.032 +/-0.010 .032 /	<u></u>						

Measured by:	Audited by:	ال	Prototype Approval:	N/A
Date: 09/05/02	Date:	09/05/01	Date:	N/A


A 03.11.12 New Issue P/O D3183-043 KJ/RF B 04.03.15 Changes as per revision C KJ/JLM/RF C 06.03.09 Dwg Rev update KJ/JLM	Approved	Revised by	-	Change	Date	Rev
C 06 03 09 Dwg Pey undete		KJ/RF	P/O D3183-043	New Issue	03.11.12	Α
C 06.03.09 Dwg Rev update KJ/JLM		KJ/JLM/RF	ision C	Changes as per rev	04.03.15	В
		KJ/JLM		Dwg Rev update	06.03.09	С
D 08.01.28 0.182 dimension removed KJEC/DD		KJEC/DD A	moved	0.182 dimension rea	08.01.28	D






	DESIGN DRAWN BY		DRAWN BY	DART AEROSPACE L HAWKESBURY, ONTARIO, CAN	
1	CHECK	ED.	APPROVED	DRAWING NO.	REV. C
ŧ	-	#	#	D3183	SHEET 1 OF 4
	DATE			TITLE	SCALE
		04.0	2.17	BRACKET ASSEMBLY	1:1
	Α	0:	3.01.24	NEW ISSUE	
	В	0:	3.06.17	REMOVE BEARING; 1.012 WS 0.882	
	С	.0	4.02.17	ADD -045/-9: 0.182 WAS 0.431	


04.11.09 . 0.830 WAS C.850



D3121-21 BOLT (1)




D3183-041 BRACKET ASSEMBLY (SHOWN) D3183-042 BRACKET ASSEMBLY (OPPOSITE) D3183-043 BRACKET ASSEMBLY (SIMILAR) D3183-044 BRACKET ASSEMBLY (SIMILAR)



D3183-5 BEARING: SPECIFICATION CONTROL DRAWING

- 1) SINGLE ROW, DEEP GROOVE, CONRAD TYPE, SHIELDED
- 2) POSSIBLE SUPPLIER: NSK P/N 6800ZZ
- 3) ALL DIMENSIONS ARE IN INCHES




D3183-7 WASHER

- 1) MATERIAL: AISI 303 ROUND BAR (M303R) **ANNEALED**
- 2) BREAK ALL SHARP EDGES 0.005 TO 0.010
- 3) TOLERANCES ARE PER DART QSI 018
- **UNLESS OTHERWISE NOTED**
- 4) ALL DIMENSIONS ARE IN INCHES

COPYRIGHT © 2003 BY DART AEROSPACE LTD.



DESIGN	DRAWN BY	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA		
CHECKED	APPROVED	DRAWING NO.	REV. C	
11		D3183	SHEET 4 OF 4	
DATE	*	TITLE	SCALE	
04	.02.17	BRACKET ASSEMBLY	1:1	



COPYRIGHT © 2003 BY DART AEROSPACE LTD.

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.